New aerosol models for the retrieval of aerosol optical thickness and normalized water-leaving radiances from the SeaWiFS and MODIS sensors over coastal regions and open oceans: publisher's note

Ziauddin Ahmad,[1,2,*] Bryan A. Franz,[1] Charles R. McClain,[1] Ewa J. Kwiatkowska,[1,3] Jeremy Werdell,[1,4] Eric P. Shettle,[5] and Brent N. Holben[1]

[1]NASA Goddard Space Flight Center, Greenbelt Road, Greenbelt, Maryland 20771, USA

[2]Science and Data Systems, Inc., 16509 Copperstrip Lane, Silver Spring, Maryland 20906, USA

[3]Science Applications International Corporation, 10260 Campus Point Drive, San Diego, California, 92121, USA

[4]Science Systems and Application, Inc., 10210 Greenbelt Road, Lanham Maryland 20706, USA

[5]Naval Research Laboratory, Washington, DC 20375, USA

*Corresponding author: Ziauddin.Ahmad@nasa.gov

Received 14 December 2010; accepted 14 December 2010;
posted 14 December 2010 (Doc. ID 139706); published 2 February 2011

Table 1 of Appl. Opt. **49**, 5455 (2010) is corrected in this publisher's note. ©2011 Optical Society of America
OCIS codes: 070.4550, 070.6110, 120.5050.

In Ref. [1] the values presented in Table 1 are incorrect. The table is presented below as originally submitted.

References

1. Z. Ahmad, B. A. Franz, C. R. McClain, E. J. Kwiatkowska, J. Werdell, E. P. Shettle, and B. N. Holben, "New aerosol models for the retrieval of aerosol optical thickness and normalized water-leaving radiances from the SeaWiFS and MODIS sensors over coastal regions and open oceans," Appl. Opt. **49**, 5545–5560 (2010).

Table 1. Complex Refractive Index Values for Different Constituents of the Fine and Coarse Mode Aerosols for SeaWiFS Sensor at Relative Humidity Rh = 0 (SF79).

Wavelength (nm)	Water-Soluble	Dustlike	Sea Salt	Soot	Water
412	$1.530 - 0.0050i$	$1.530 - 0.0080i$	$1.500 - 0.0000i$	$1.750 - 0.4586i$	$1.338 - 0.0000i$
443	$1.530 - 0.0050i$	$1.530 - 0.0080i$	$1.500 - 0.0000i$	$1.750 - 0.4551i$	$1.337 - 0.0000i$
490	$1.530 - 0.0050i$	$1.530 - 0.0080i$	$1.500 - 0.0000i$	$1.750 - 0.4500i$	$1.335 - 0.0000i$
510	$1.530 - 0.0050i$	$1.530 - 0.0080i$	$1.500 - 0.0000i$	$1.750 - 0.4500i$	$1.334 - 0.0000i$
555	$1.530 - 0.0060i$	$1.530 - 0.0080i$	$1.499 - 0.0000i$	$1.750 - 0.4394i$	$1.333 - 0.0000i$
670	$1.530 - 0.0066i$	$1.530 - 0.0080i$	$1.490 - 0.0000i$	$1.750 - 0.4300i$	$1.331 - 0.0000i$
765	$1.526 - 0.0091i$	$1.526 - 0.0080i$	$1.486 - 0.0000i$	$1.750 - 0.4300i$	$1.330 - 0.0000i$
865	$1.520 - 0.0121i$	$1.520 - 0.0080i$	$1.480 - 0.0000i$	$1.750 - 0.4303i$	$1.329 - 0.0000i$

0003-6935/11/050626-01$15.00/0
© 2011 Optical Society of America