Carnegie Mellon

The Human Body as an Interactive Computing Platform

Chris Harrison

Carnegie Mellon

Carnegie Mellon
Fit in your pocket / bag
Communicate
Create
Access information
Play Angry Birds
NOKIA
3

Carnegie Mellon

SCR-300

1943



Carnegie Mellon

Motorola DynaTAC 8000x

1983

Apple iPod Touch

2007

Computing Factors



Computing Factors



Computing Factors



Computing Factors



Small + Powerful
Carnegie Mellon
12

Carnegie Mellon

Why not this?



Carnegie Mellon

Human Factors

Human Factors

- Finger size



Human Factors

- Finger size
- Visual acuity



Human Factors

- Finger size
- Visual acuity
- Manual dexterity
- …

Mobile Device Size



Mobile Device Size



Carnegie Mellon
mobile device
limited surface area
20

Carnegie Mellon


1
2
3
4
5
6
7
8
Scale





Touchscreen

Button

Physical controls


Carnegie Mellon
Touchscreens



Touchscreens



Touchscreens

mobile device
=
=
limited input richness

Carnegie Mellon

Input Richness

x Input Area

= Input Power


Improving Mobile Interaction
Increasing Interaction Richness
Capturing Addition Input Dimensions
Lean and Zoom (CHI 2008)
Stacking Tangibles (ITS 2009)
SurfaceMouse (TEI 2011)
TapSense (UIST 2011)
Shear Input (CHI 2012)
Increasing Interaction Area
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)
Appropriating the Human Body
Skinput (CHI 2010)
OmniTouch (UIST 2011)


Improving Mobile Interaction
Increasing Interaction Richness
Increasing Interaction Area


Improving Mobile Interaction
Increasing Interaction Richness
Increasing Interaction Area


Increasing Interaction Richness
Capturing Addition Input Dimensions
Lean and Zoom (CHI 2008)
Stacking Tangibles (ITS 2009)
SurfaceMouse (TEI 2011)
TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing
Moving Interaction Into Freespace

Carnegie Mellon

TapSense

UIST 2011

Chris Harrison Julia Schwarz Scott Hudson

Carnegie Mellon

Shear Input

CHI 2012

Chris Harrison Scott Hudson


Carnegie Mellon
Touch X,Y: 910,337


Increasing Interaction Richness
Capturing Addition Input Dimensions
Lean and Zoom (CHI 2008)
Stacking Tangibles (ITS 2009)
SurfaceMouse (TEI 2011)
TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing
Moving Interaction Into Freespace


Improving Mobile Interaction
Increasing Interaction Richness
Increasing Interaction Area


SurfaceMouse (TEI 2011)
TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)
[Baudisch '09, Wigdor '07]

Carnegie Mellon

Cord Input

CHI 2010

Julia Schwarz Chris Harrison Jennifer Mankoff Scott Hudson


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)

Carnegie Mellon

Abracadabra

UIST 2009

Chris Harrison Scott Hudson

SONGS
>>
<<
PAUSE


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)

Carnegie Mellon

Scratch Input

UIST 2008

Chris Harrison Scott Hudson


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)



Carnegie Mellon

The Human Body as an Interactive Computing Platform

- Goes where we go
- Always-available input
  [Tan 2010, Saponas 2009]
- Skin is the largest organ
  - Two square meters of surface area
  - Hand alone offers more surface area than a smartphone
- Kinesthetic senses
  - Rapidly and accurately position our body
  - Fine tuned muscle memory, hand eye coordination
  - Eyes free interaction


TapSense (UIST 2011)
Shear Input (CHI 2012)
Using Unused Surface Area
Cord Input (CHI 2010)
PocketTouch (UIST 2011)
Increasing Interaction Area
Moving Interaction Into Freespace
Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)
Appropriating Surface Area
Scratch Input (UIST 2008)
Minput (CHI 2010)

Using Unused Surface Area

Cord Input (CHI 2010)
PocketTouch (UIST 2011)

Moving Interaction Into Freespace

Abracadabra (UIST 2009)
Whack Gestures (TEI 2010)

Appropriating Surface Area

Scratch Input (UIST 2008)
Minput (CHI 2010)

Appropriating the Human Body

Skinput (CHI 2010)
OmniTouch (UIST 2011)

Carnegie Mellon

Skinput

CHI 2010

Chris Harrison Desney Tan Dan Morris

Acoustic Sensing

- Enhanced transmission through solids/liquids
  - Longer transmission distances
  - Better preservation of signal (high SNR)
- Intra-object acoustics less prone to outside interference
- Allows surfaces to be appropriated
  - Remote, indirect sensing
  - Without permanent instrumentation

Taps on the Body

- Input is by tapping on body, like touchscreen
- Taps on body create unique acoustic signatures
- Signature affected by:
  - Density of tissues
  - Anatomical features
  - Joints



Taps on the Body

- Input is by tapping on body, like touchscreen
- Taps on body create unique acoustic signatures
- Signature affected by:
  - Density of tissues
  - Anatomical features
  - Joints



Carnegie Mellon

Acoustics on the Body



Longitudinal (compression) waves

Acoustics on the Body



Transverse surface distortions (ripples)

Sensing

- Cantilevered mass on piezo film
  - Mass alters resonant frequency
  - Resonant frequency amplifies energy
  - Natural band pass filter
- We use 10 sensing elements
  - In two arrays of five
  - Acoustic spectrum from 25 to 78 Hz
- Constructed prototype Armband




Tacoma Narrows Bridge
1940



Upper Array	25 Hz	27 Hz	30 Hz	38 Hz	78 Hz
Lower Array	25 Hz	27 Hz	40 Hz	44 Hz	64 Hz




Pico-Projector
Projected Interface
Sensing Armband


SAMSUNG

Segmentation and Processing

- Sensors provide high level of noise suppression
  - Segment using fixed thresholds on the exponential average
- Sensors provide acoustic information in different bands
  - Derive band ratios, frequency distributions, other features
- Train SVM classifier; use to determine location of tap

[Witten '05]

- Bind functions to different locations


Current input: thumb (0)
Total: 0
SAMSUNG
Training Skinput Classifier on Finger
(5 taps per finger, 25 examples total)


tetris

Carnegie Mellon

Experiment

- 13 Participants (7 female)
- Age ranged from 20 to 56 (mean 38)
- BMI ranged from 20.5 (normal) to 31.9 (obese)
- Three input location sets
  - Fingers (5 locations)
  - Whole arm (5 locations)
  - Forearm (10 locations)

Procedure

- Users provided 3 rounds of example input
  - 10 taps to each input location
  - Next round started after all locations were tapped
- Accuracy evaluated:
  - Presented users a simple text stimuli (e.g., “tap your wrist”)
  - Each input location appeared 10 times, random order
  - Live segmentation and classification accuracy

Carnegie Mellon

Fingers (5 locations)

- We have exceptional dexterity with our fingers
- Discrete and named (e.g., thumb, ring)
- Linearly ordered
- Downside: Hard to sense

- Mean accuracy: **87.7%** (SD=10.0%)
- Segmentation accuracy: **~100%**

Carnegie Mellon

Fingers (5 locations)

- We have exceptional dexterity with our fingers
- Discrete and named (e.g., thumb, ring)
- Linearly ordered
- Downside: Hard to sense

- Mean accuracy: **87.7%** (SD=10.0%)
- Segmentation accuracy: **~100%**

Carnegie Mellon

Whole Arm (5 locations)

- Discrete and well named (e.g., wrist, palm)
- Acoustically unique

- Mean accuracy: **95.5%** (SD=5.1%)
- Eyes-free mean accuracy: **85.0%** (SD=9.4%)

Carnegie Mellon

Whole Arm (5 locations)

- Below-elbow mean accuracy:
  95.5% (SD=5.1%)
- Above-elbow mean accuracy:
  88.3% (SD=7.8%)



Carnegie Mellon

Forearm (10 locations)

- Attempt to tax system accuracy
- Used stickers instead of names
- Two training rounds (due to time)

- Mean accuracy: **81.5%** (SD=10.5%)

Carnegie Mellon

Forearm Groupings & Accuracies



81.5% (10 locations)

84.0% (5 locations)

86.3% (5 locations)

87.1% (6 locations)

87.4% (5 locations)

88.8% (6 locations)

91.2% (4 locations)

Walking and Jogging

- Male participant
  - 2.3 mph walking
  - 4.3 mph jogging
- Female participant
  - 1.9 mph walking
  - 3.9 mph jogging
- Three Input locations:
  - Arm | Wrist | Palm
  - Provided 10 input examples per location while walking/jogging

Walking and Jogging

Walking

- No false positive inputs
- **100%** true positive segmentation
- Mean classification accuracy **93.4%**

Jogging

- Four false positives (over six minutes)
- **100%** true positive segmentation
- Mean classification accuracy **71.7%**

MENU

Vitamins
Energy Players
Supplements

Address Book
Music Player

Carnegie Mellon

OmniTouch

UIST 2011

Chris Harrison Hrvoje Benko Andy Wilson

picoP


Depth Camera
Pico Projector





FPS: 29.95




ID: 156
Prob: 45
ID: 151
Prob: 44
ID: 152
Prob: 47

Identifying Surfaces

- Find candidate surfaces for projection
- 3D connected components
- Compute real world size
  - Surfaces smaller than a hand are discarded
- Compute surface X/Y/Z position and orientation

Identifying Surfaces



Depth Map

3D Connected Components

Projected Interfaces

- Compositing interfaces in virtual 3D scene
  - Treat interfaces as planes in 3D space
  - Treat projector like a virtual camera; project viewport image
  - Scaling, z-ordering, perspective transformation, etc. comes for free
  - Ray cast fingers as input points onto active interfaces
- Requires projector/camera calibration
  - Convert 3D spatial coordinates to 2D projected points
    [DeMenthon '95, Wilson '10]
- Interfaces can be authored in real-world units and coordinates


Slide to Unlock

Defining Interactive Areas

- Projected interfaces
  - Where to center?
  - How tall/wide?
- Approaches
  - One-size fits all
  - Classification driven
  - User defined




User Defined Interfaces

Carnegie Mellon

Evaluation

12 Participants (6 female)

9 Targets (3x3 pattern); random order

4 Surfaces (hand, arm, pad, wall)

3 Distances (hand, pad conditions)

6048 “Clicks” collected

Evaluation

Hand on body

Arm curved, additional on body surface

Pad object held in hand

Wall fixed surface in the environment


mm
10
20
30
40
50
60
70
80
90
100
mm
10
20
30
40
50
60
70
80
90
100










10 20 30 40 50 60 70 80 90 100
10 20 30 40 50 60 70 80 90 100


10 20 30 40 50 60 70 80 90 100
10 20 30 40 50 60 70 80 90 100


10 20 30 40 50 60 70 80 90 100
10 20 30 40 50 60 70 80 90 100


10
20
30
40
50
60
70
80
90
100
10
20
30
40
50
60
70
80
90
100

“Click” Precision



OmniTouch

[Holz and Baudisch '10]

“Click” Precision



OmniTouch

[Holz and Baudisch '10]

“Click” Precision



OmniTouch

[Holz and Baudisch '10]

Carnegie Mellon

“Click” Detection

- Of our 6048 crosshair “click” trials:
  - **96.5%** correctly had one click event
  - **0.8%** had no click event (i.e., system missed click)
  - **2.5%** had two click events
  - **0.1%** had three click events

- With a 500ms timeout click rejection:
  - **98.9%** click detection accuracy

Drag Spatial Accuracy



- No significant difference in X, Y, 1D, 2D trials
- Mean deviation of **6.3mm** (mean SD=3.9mm)

Carnegie Mellon

Armura

TEI 2012

Chris Harrison Shilpa Ramamurthy Scott Hudson

Interface Design



Interface Design



Menuing (gestures)



Menuing (gestures)



Carnegie Mellon
Menuing (gestures + position)

Menuing (gestures + position)



Menuing (gestures + position)

Carnegie Mellon
Modal Layout and Control

Next steps



- What are ideal on-body surfaces?
- Friends/strangers using on-body interfaces?
- How do users feel about projected Interfaces?
- Where is it appropriate to touch own body?
- Where should interfaces be located?
- How should they be laid out?

Carnegie Mellon

Next steps



Carnegie Mellon

Thank You

Chris Harrison
chris.harrison@cs.cmu.edu
www.chrisharrison.net

This work was supported in part by a Microsoft Research Ph.D. Fellowship and grants from the Intel Research Council, General Motors, the National Science Foundation under grants IIS-0713509. IIS-0803733, and IIS-0840766, and finally, the Center for Future Work, Heinz College, Carnegie Mellon University.